



| | |
|------------------|-------------------------------|
| SECTION 1 | PRODUCT IDENTIFICATION |
|------------------|-------------------------------|

Product name : **REXCO 20 – Ultimate Hand Cleaner**
Cross reference : Mechanic Hand Cleaner
Address : Rexco Solution Technique
711 S. Carson Street Suite#4
Carson City, NV, 89701
Phone number : (775)434-0273

| | |
|------------------|------------------------------|
| SECTION 2 | HAZARDOUS INGREDIENTS |
|------------------|------------------------------|

| Chemical name | CAS Number | Percent | OSHA PEL |
|---------------------------------|--------------|---------|---------------------|
| Aliphatic Solvent, hydrotreated | : 64742-47-8 | <30 | 300 ppm |
| Glycerin | : 56-81-5 | <3 | 10mg/m3 |
| Propylene Glycol | : 57-55-6 | <3 | 0.34mg/m3TWA (skin) |
| Surfactant nonionic/cationic | : N/A | -- | -- |

| | |
|------------------|-------------------------------|
| SECTION 3 | HAZARDS IDENTIFICATION |
|------------------|-------------------------------|

Health Hazards : May be harmful if ingested. High Vapor may be irritation to eyes and respiratory tract. See section 11 for further information
Physical Hazards : Not detected.

| | |
|------------------|---------------------------|
| SECTION 4 | FIRST AID MEASURES |
|------------------|---------------------------|

Emergency First Aid Procedures:
Eye contact : Irritant to eye, flush immediately with large amount of water for 15 minute, get medical attention.
Skin contact : In general situation, no irritant observed, If irritant occur, get medical attention.
Inhalation : Remove to fresh air.
Ingestion : Call physician immediately, Don't give anything to mouth to unconscious person.

| | |
|------------------|-------------------------------|
| SECTION 5 | FIRE FIGHTING MEASURES |
|------------------|-------------------------------|

EXTINGUISHING MEDIA : Foam, water spray(fog), dry chemical, and carbon dioxide. Water spray can be used to cool and protect containers exposed to heat and flame.
SPECIFIC METHODS/ PROTECTION OF FIREFIGHTERS: Wear suitable protective equipment.
Hazardous product combustion : Oxide of carbon, oxide of nitrogen.
Mechanical Sensitivity : none reasonable foreseeable
Sensitivity to static discharge : Sensitivity to static discharge is not expected
Unusual Fire/Explosion Hazards : Does not sustain combustion (ASTM D 4206)
Lower Explosive Limit : Not Determined
Upper Explosive Limit : Not Determined

| | |
|------------------|-------------------------------------|
| SECTION 6 | ACCIDENTAL REALEASE MEASURES |
|------------------|-------------------------------------|

Spills may cause slippery floors. Prevent spill from entering drainage/sewer systems, waterways and surface water. Notify local health authorities and other appropriate agencies if such contamination occurs.

PERSONAL PRECAUTIONS: Personnel protective equipment must be worn (See Section 8). Minimize contact with skin and clothing.

SECTION 7 HANDLING AND STORAGE

Keep out of reach of Children. Keep containers tightly closed in a cool, well-ventilated place. Store below 50 °C. Do not allow freezing.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**PERSONAL PROTECTIVE EQUIPMENT**

RESPIRATORY PROTECTION: Not required under normal use

HAND PROTECTION: Use chemical-resistant gloves to avoid prolonged or repeated skin contact.

EYE PROTECTION: Wear chemical splash goggles with side shields or face shield.

SKIN AND BODY PROTECTION: Long sleeve shirt is recommended. Use of chemical-resistant apron or other impervious clothing recommended. Chemically resistant boots are also recommended. Launder clothing before reuse.

HYGIENE MEASURES: Minimize breathing vapor, mist or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period.

SECTION 9 PHYSICAL DATA

| | |
|---------------------|-----------------------------------|
| Flash Point | : none |
| Freezing Point | : 0 °C |
| Boiling Point | : 100°C |
| Solubility in water | : Soluble |
| Appearance & odor | : Milky white -Viscous, fragrance |
| Spec Gravity | : 0.95 |
| pH | : 5.49 |

SECTION 10 REACTIVITY DATA

| | |
|---------------------------------|--|
| Stability | : Stable as long as container is tightly close and put in dry area |
| Incompatibility | : Avoid contact with strong oxidizing material, avoid contact with heat sources. |
| Hazardous Decomposition product | : Oxides of carbon. |
| Hazardous polymerization | : Will not occur. |

SECTION 10 TOXICOLOGICAL INFORMATION

PRIMARY ROUTES OF ENTRY OR EXPOSURE: Skin absorption, eye contact, inhalation and ingestion.

INHALATION: Vapor concentrations above recommended exposure limits are irritating to the eyes and respiratory tract. May cause headaches and dizziness, are anesthetic and may have other central nervous system effects, including death based on data from components or similar materials.

SKIN: Slightly irritating to the skin. Prolonged and repeated contact may result in various skin disorders such as dermatitis. Skin contact may aggravate existing dermatitis condition based on data from components or similar products.

EYE: May cause eye irritation based on data from components or similar products.

INGESTION: Ingestion of material may result in vomiting; Aspiration (breathing of vomit us into the lungs) must be avoided as even small quantities may result in aspiration pneumonitis. Ingestion may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea and abdominal pain.

ACUTE TOXICITY: Pre-existing skin and respiratory disorders may be aggravated by exposure.

SECTION 12 ECOLOGICAL INFORMATION

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate and remove with inert absorbent. Pick up large spill with vacuum tracks or pump. Absorb small spills/leaks with oil absorbent. Follow local and government regulation regarding disposal.

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in an environmentally safe manner and in accordance with governmental regulations.

SECTION 14 TRANSPORTATION INFORMATION

Ground Transport (DOT)

DOT Not Regulated

Hazards Class None

UN/ID number None

TRANSPORTATION INCIDENT INFORMATION: For further information relative to spills resulting from transportation incidents, refer to latest Department of Transportation Emergency Response Guidebook for Hazardous Materials Incidents.

SECTION 15 REGULATORY INFORMATION

SARA 302 Extremely Hazardous : None

TSCA Inventory Status : all components of this product are listed (or exempt) on the EPA

TSCA inventory

SECTION 16 OTHER INFORMATION

Health 2, Flammability 0 (propellant), Physical hazards 1, Personal protection B

The information and recommendation herein are, to the best of our knowledge and belief, accurate and reliable as of the date issued. PT. Altama Surya Anugerah. does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.
