

SECTION 1**PRODUCT IDENTIFICATION**

Product name : **Rexco 82 Spare Part & Brake Cleaner**
Cross reference : Brake Parts Cleaner Spray
Address : PT Altama Surya Anugerah
Jl. Bandengan Utara 85A no. 4
Jakarta, 14440, Indonesia

SECTION 2**HAZARDOUS INGREDIENTS**

Chemical name	CAS Number	Percent	TLV
2-Propanone	: 67-64-1	25-45	500 ppm
2-Methylbenzene	: 98-19-1	<25	100 ppm
Methylbenzene	: 108-88-3	<25	20 ppm

SECTION 3**HAZARDS IDENTIFICATION**

Health Hazards : May cause serious eye damage/eye irritation. May potentially be harmful to human reproductive system. May potentially be harmful to organs.
Physical Hazards : Combustible liquid. Flammable aerosol. Gas under pressure. Liquid or vapor may ignite. Keep away from all sources of ignition

GHS Label Elements



Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs (liver, kidneys, brain, lungs) through prolonged or repeated exposure. Harmful to aquatic life.

SECTION 4**FIRST AID MEASURES**

Routes of exposure and effects of overexposure:

Inhalation : May cause dizziness and nausea.
Skin Contact : May cause light irritation for sensitive skin.
Ingestion : Do not ingest.

Emergency First Aid Procedures:

Eye contact : Serious irritant to eye, flush immediately with large amount of water for 15 minutes, get medical attention.
Skin contact : May cause irritant to sensitive skin, rinse thoroughly with water, remove contaminated clothing and shoes immediately. if irritant occur, get medical attention.
Inhalation : Remove to fresh air.
Ingestion : Call physician immediately, do not give anything to mouth to unconscious person.

SECTION 5**FIREFIGHTING MEASURES**

EXTINGUISHING MEDIA: Foam, water spray(fog), dry chemical, and carbon dioxide. Water spray can be used to cool and protect containers exposed to heat and flame.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible liquid. Can form combustible mixtures at temperatures at / or above flashpoint. Materials can accumulate static charges, which can cause an incendiary electrical discharge. Toxic fumes or vapors may evolve on burning. This liquid is volatile and gives off invisible vapors. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights or other flames and ignition sources at locations distant from material handling point. Container may rupture on heating.

SPECIFIC METHODS/ PROTECTION OF FIREFIGHTERS: Do not enter confined fire space without full Bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive-pressure NIOSH approved self-contained breathing apparatus. Isolate "fuel" supply from fire. Avoid spraying water directly into storage containers due to danger of boil over.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS: Thermal decomposition products are highly dependent on the combustion conditions. A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Fumes, smoke, carbon monoxide and other products of incomplete combustion may be found upon combustion.

SECTION 6**ACCIDENTAL REALEASE MEASURES**

PERSONAL PRECAUTIONS: Personnel protective equipment must be worn (See Section 8). Minimize contact with skin and clothing.

ENVIRONMENTAL PRECAUTIONS: Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Assure conformity with applicable governmental regulations.

METHODS FOR CLEANING UP: Ventilate spill area if in confined or poorly ventilated area. Pick up free liquid with explosion proof or hand pump for recycle and/or disposal. Residual material can be absorbed on inert material. Do not use combustible materials such as sawdust.

SECTION 7**HANDLING & STORAGE**

TECHNICAL MEASURES: Keep containers closed when not in use. Do not store near heat, sparks, flame or strong oxidants.

PREVENTION OF USER EXPOSURE: Avoid contact with eyes. Avoid prolonged or repeated contact with skin and clothing. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

PREVENTION OF FIRE AND EXPLOSION: Refer to Section 5.

PRECAUTIONS: Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

SAFE HANDLING ADVICE: Refer to Section 10. **STORAGE**

TECHNICAL MEASURES: Keep containers closed when not in use. Do not store near heat, sparks, flame or strong oxidants.

STORAGE CONDITIONS: Store in a cool, dry ventilated area. Keep containers tightly closed and upright when not in use.

INCOMPATIBLE PRODUCTS: Refer to Section 10.

PACKAGING MATERIALS: The original Prolong container is the recommended storage material for this product.

SECTION 8**EXPOSURE CONTROLS / PERSONAL PROTECTION****ENGINEERING MEASURES**

CONTROL PARAMETERS: The use of local exhaust ventilation is recommended to control process emissions near source. Laboratory samples should be stored and handled in lab hood. Provide mechanical ventilation of confined spaces. No smoking. Keep away from flame or other ignition sources.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: Use NIOSH/MSHA approved full face respirator with a combination organic vapor and IGH efficiency filter cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, poorly ventilated areas and for large spill clean-up sites.

HAND PROTECTION: Use chemical-resistant gloves to avoid prolonged or repeated skin contact.

EYE PROTECTION: Wear chemical splash goggles with side shields or face shield.

SKIN AND BODY PROTECTION: Long sleeve shirt is recommended. Use of chemical-resistant apron or other impervious clothing recommended. Chemically resistant boots are also recommended. Launder clothing before reuse.

HYGIENE MEASURES: Minimize breathing vapor, mist or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period.

SECTION 9**PHYSICAL DATA**

Flash Point (COC)	<1°C
Kinematic viscosity @27°C	0.481 cSt
Solubility in water	No
Vapor density	N/A
Appearance & odor	Clear transparent, solvent odor
Spec Gravity @27° C	0.8029
Boiling Point	143.2° C
pH	5.87
Color ASTM	L 0.5

SECTION 10**REACTIVITY DATA**

Stability	: Stable as long as container is tightly close and put in dry area
Incompatibility	: Avoid contact with strong oxidizing material, avoid contact with heat sources.
Hazardous Decomposition product	: Oxides of carbon.
Hazardous polymerization	: Will not occur.

SECTION 11**TOXICOLOGICAL INFORMATION**

PRIMARY ROUTES OF ENTRY OR EXPOSURE: Skin absorption, eye contact, inhalation and ingestion. **INHALATION:** Vapor concentrations above recommended exposure limits are irritating to the eyes and respiratory tract. May cause headaches and dizziness, are anesthetic and may have other central nervous system effects, including death based on data from components or similar materials.

SKIN: Slightly irritating to the skin. Prolonged and repeated contact may result in various skin disorders such as dermatitis. Skin contact may aggravate existing dermatitis condition based on data from components or similar products.

EYE: May cause eye irritation based on data from components or similar products.

INGESTION: Ingestion of material may result in vomiting; Aspiration (breathing of vomitus into the lungs) must be avoided as even small quantities may result in aspiration pneumonitis. Ingestion may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea and abdominal pain.

ACUTE TOXICITY: Pre-existing skin and respiratory disorders may be aggravated by exposure.

Date : 7 March 2024

SECTION 12 ECOLOGICAL INFORMATION

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate and remove with inert absorbent. Pick up large spill with vacuum trucks or pump. Absorb small spills/leaks with oil absorbent. Follow local and government regulation regarding disposal.

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in an environmentally safe manner and in accordance with governmental regulations.

SECTION 14 TRANSPORTATION INFORMATION

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class:	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

DOT CLASSIFICATION: NA1993,NOS (AROMATIC HYDROCARBON),PGIII,3 COMBUSTIBLE LIQUID
DOT BULK SHIPPING CLASSIFICATION: NA1993,NOS (AROMATIC HYDROCARBON),PGIII,3 IMDG CODE:
NA1993,NOS (AROMATIC HYDROCARBON),PGIII,3

TRANSPORTATION INCIDENT INFORMATION: For further information relative to spills resulting from transportation incidents, refer to latest Department of Transportation Emergency Response Guidebook for Hazardous Materials Incidents.

SECTION 15 REGULATORY INFORMATION

THE FOLLOWING INFORMATION MAY BE USEFUL IN COMPLYING WITH VARIOUS STATE AND FEDERAL LAWS AND REGULATIONS UNDER VARIOUS ENVIRONMENTAL STATUTES: THRESHOLD PLANNING QUANTITY (TPQ), EPA REGULATION 40 CFR 355 (SARA SECTIONS

301-304): No TPQ for product or any constituent greater than 1% or 0.1% (carcinogen) for SARA Section 302.

TOXIC CHEMICAL RELEASE REPORTING, EPA REGULATION 40 CFR 372 (SARA SECTION 313): This product contains the following substances subject to the reporting requirements of SARA III Section 313 1986 and 40

TSCA INVENTORY: All components are listed on the TSCA inventory. WHIMIS: Class B, Division 3, Combustible liquids

IMO: CLASS 3: Flammable liquid

NOTE: State and local regulatory requirements may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding other regulatory requirements.

SECTION 16 OTHER INFORMATION

The information and recommendation herein are, to the best of our knowledge and belief, accurate and reliable as of the date issued. PT Altama Surya Anugerah does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.